


Branched Vinyl Silicone Oil

SK-BRVO-25000



Product Description:

● This product is an organosilicon polymer with a unique branched structure. Its molecular design features a tetrafunctional Q core, with four directions extending into dimethylsiloxane D segments, terminated by vinyl groups. This branched vinyl silicone oil exhibits high reactivity and thermal stability, making it widely used in liquid silicone rubber and silicone pressure-sensitive adhesives.

Specifications:

Test Item	Typical Data	Test Standard/Instrument
Appearance	Colorless to slightly yellow transparent liquid	Visual inspection
Viscosity (mPa.s/25℃)	20000~30000	GB/T 10247-2008
Refractive Index (25℃)	1.40~1.41	GB/T 6488
Density (g/cm ³)	0.96~0.98	GB/T 4472
Volatile Content (wt%)	≤0.5	150℃/3H

Typical Applications:

- **Liquid Silicone Rubber:** The branched structure provides fast curing speed and mechanical strength.
- **Silicone Pressure-Sensitive Adhesives:** Used in protective tapes/films, offering low adhesion and excellent wettability.

Packaging & Storage:

- SK-BRVO-25000 is packaged in 200KG iron drums.
- Store at room temperature, in a dry and dark place.
- This product is non-flammable and non-explosive, and should be transported as non-hazardous goods.
- Best used within 12 months from the production date. If expired, re-inspect and use only if qualified.

Safety & Environmental:

- Ensure proper protective equipment is worn when handling this product. Refer to the Material Safety Data Sheet (MSDS) for details.
- Dispose of packaging according to local solid waste regulations.

Notes:

- The information provided in this document is based on reliable data from our company. Product specifications and performance may change without prior notice.
- The information is derived from laboratory and practical experience and is for reference only. Since conditions and methods of use are beyond our control, application testing is recommended before use.
- Some performance parameters of the product can be adjusted according to customer requirements. If needed, please contact our technical department engineers.
